



# C5e KEYSTONE JACK UTP 50U



**Performance:**  
Meets C5e EIA/TIA 568B Standard.

**Materials:**

Body : Fireproof ABS UL-94V0  
 Jack : 8P8C 50 micro inches gold plated  
 PCB : FR-4 / UL-94V0  
 IDC Body : Fireproof ABS UL-94V0  
 IDC Pin : Bronze & Tinned  
 IDC Description : For 22-26 AWG.  
 For 110 or Krone punch-down Tool

**Electrical Specifications:**


Insulation Resistance : 500M ohms (min.)  
 Contact Resistance : 20m ohms (max.)  
 Current Rating : 1.5 Amps .  
 DC Resistance : 0.1 ohms (max.)  
 Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

**Mechanical Specifications:**


IDC Punch Down Cycle : Over 250 Cycles (min.)  
 Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

**Dimensions : m/m**



16.3




**Color coding information**

- T568A:
- 1—WH/GN
  - 2—GN
  - 3—WH/OR
  - 4—BL
  - 5—WH/BL
  - 6—OR
  - 7—WH/BR
  - 8—BR


**Printed Letter :**

Printed Letter:(Blue Ink)

Cat.5e




KJ2



23.3



23.3



DRAW NO:	APPR	CUSTOMER:	DA101
UNIT: m/m	CHECK	ITEM NO:	
SCALE:	DESIGN	DATE:	
		TOLERANCE: · ± 1 · X ± 0.1 · XX ± 0.15	

**AMDEX**