



Cat.3 Jack



Marking : Phone



Printed Letter :



Cat.3
6P4C

N3674

Performance :

Materials:	:	Fireproof ABS UV-94V0
Plastic Body	:	6P4C 50 micro inches gold plated
RJ-45 Jack	:	FR-4 / 1.0mm UL-94V0
PCB	:	Fireproof ABS UL-94V0
IDC Body	:	Bronze & Tinned
IDC Pin	:	

IDC Description : For 22-26 AWG.

For 110 or Krone punch-down Tool

Electrical Specifications :

Insulation Resistance:	500M ohms (min.)
Contact Resistance :	20m ohms (max.)
Current Rating :	1.5 Amps.
DC Resistance :	0.1 ohm (max.)
Withstanding Voltage:	1000 VAC RMS @ 60Hz / 1 min.


Mechanical Specifications:

IDC Punch Down Cycle :	Over 250 Cycles (min.)
RJ-45 Jack Insertion Cycle:	Over 2000 Cycles (min.)
Operation Temperature :	-40 ~ +70 degree / C


Description:

Cat.3 unshielded, Clipsal keystone jack with Phone logo


Dimensions : m/m




21.2




23.6



29



Wire Map:



DRAW NO:		ITEM NO:	DT1006P
UNIT:	APPR	G.O.	CUSTOMER:
SCALE:	CHECK	DESIGN	DATE:
1:1			TOLERANCE: ± 1 · X ± 0.2 · XX ± 0.15