



# Cat.3 Jack



Marking : Phone



Printed Letter :

8P4C

N3674

HJ1



**Materials:**

- Plastic Body : Fireproof ABS UL-94V0
- RJ-45 Jack : 8P4C 15 micro inches gold plated
- PCB : FR-4 / 1.0mm UL-94V0
- IDC Body : Fireproof ABS UL-94V0
- IDC Pin : Bronze & Tinned

**IDC Description :** For 22-26 AWG.

For 110 or Krone punch-down Tool

**Electrical Specifications :**

- Insulation Resistance: 500M ohms (min.)
- Contact Resistance : 20m ohms (max.)
- Current Rating : 1.5 Amps.
- DC Resistance : 0.1 ohm (max.)
- Withstanding Voltage: 1000 VAC RMS @ 60Hz / 1 min.


**Mechanical Specifications:**

- IDC Punch Down Cycle : Over 250 Cycles (min.)
- RJ-45 Jack Insertion Cycle: Over 2000 Cycles (min.)
- Operation Temperature : -40 ~ +70 degree / C

**Description:**


Cat.3 unshielded, HPM keystone jack

Dimensions : m/m




21.2



23.6



Wire Map:



29



DRAW NO:		ITEM NO:	DT100H
	APPR	G.O.	CUSTOMER:
UNIT: m/m	CHECK		DATE:
SCALE: 1:1	DESIGN	TOLERANCE: ± 1	· X ± 0.2 · XX ± 0.15