



Cat.3 Jack



Marking:AMDEX



Printed Letter :

8P2C

N3674

CJ2



Materials:

- Plastic Body : Fireproof ABS UL-94V0
- RJ-45 Jack : 8P2C 15 micro inches gold plated
- PCB : FR-4 / 1.0mm UL-94V0
- IDC Body : Fireproof ABS UL-94V0
- IDC Pin : Bronze & Timed

IDC Description : For 22-26 AWG.

For 110 or Krone punch-down Tool

Electrical Specifications :

- Insulation Resistance: 500M ohms (min.)
- Contact Resistance : 20m ohms (max.)
- Current Rating : 1.5 Amps.
- DC Resistance : 0.1 ohm (max.)
- Withstanding Voltage: 1000 VAC RMS @ 60Hz / 1 min.



Mechanical Specifications:

- IDC Punch Down Cycle : Over 250 Cycles (min.)
- RJ-45 Jack Insertion Cycle: Over 2000 Cycles (min.)
- Operation Temperature : -40 ~ +70 degree / C




Description:

Cat.3 unshielded, Clipsal keystone jack

Dimensions : m/m



Wire Map:



DRAW NO:		ITEM NO:	DT100/2
UNIT:	APPR	G.O.	CUSTOMER:
SCALE:	CHECK	DESIGN	DATE:
1:1			TOLERANCE: ± 1 · X ± 0.2 · XX ± 0.15