

# Cat.6 Jack

## Performance :



Meets Cat.6 EIA/TIA 568B.1 Standard.

## Materials:

Plastic Body : Fireproof ABS UL-94V0  
 RJ-45 Jack : 8P8C 50 micro inches gold plated  
 PCB : FR-4 / 1.0mm UL-94V0  
 IDC Body : Fireproof ABS UL-94V0  
 IDC Pin : Bronze & Tinned

Label Color Code : T568 A

Marking : AMDEX-6



Printed Letter :

Cat.6  
 N3674 CJ1





IDC Description : For 22-26 AWG.  
 For 110 or Krone punch-down Tool

## Electrical Specifications :



Insulation Resistance : 500M ohms (min.)  
 Contact Resistance : 20m ohms (max.)  
 Current Rating : 1.5 Amps.  
 DC Resistance : 0.1 ohm (max.)  
 Withstanding Voltage: 1000 VAC RMS @ 60Hz / 1 min.

Dimensions : m/m



Wire Map:

RJ-45 8P8C	IDC Block
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8



## Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)  
 RJ-45 Jack Insertion Cycle: Over 2000 Cycles (min.)  
 Operation Temperature : -40 ~ +70 degree / C

## Description:

Cat.6 unshielded, Clipsal keystone jack, with AMDEX-6 logo

DRAW NO:	ITEM NO:	DA600
	APPR	G.O.
UNIT: m/m	CHECK	DATE:
SCALE: 1:1	DESIGN	TOLERANCE: ± 1 · X ± 0.2 · XX ± 0.15